

HC-37/U or RW TO-8

Through Hole Crystals



UTE C 93-611 Standard referenced crystal codes and key specifications

Reference Crystal Code	Overtone	Nominal Frequency (MHz)	Load Capacitance (pF)	Calibration tolerance (ppm)	Frequency stability over temperature deviation (ppm)	Operating temperature range (°C)
QB 676	1	4 to 20	30	±10	±4	5 to 55
QB 677	1	4 to 20	30	±10	±4	-10 to 70
QB 678	1	4 to 20	30	±10	±25	-40 to 85
QB 679	1	4 to 20	30	±10	±30	-55 to 100
QB 680	1	3 to 20	30	±10	±5	5 to 55
QB 681	1	3 to 20	30	±10	±10	-10 to 70
QB 682	1	3 to 20	30	±10	±30	-40 to 85
QB 683	1	3 to 20	30	±10	±40	-55 to 100
QB 718	1	3 to 20	∞	±10	±30	-40 to 85
QB 719	1	3 to 20	∞	±10	±40	-55 to 100
QB 720	1	3 to 20	30	±10	±30	-40 to 85
QB 721	1	3 to 20	30	±10	±40	-55 to 100
QB 692	3	20 to 60	∞	±10	±4	5 to 55
QB 693	3	20 to 60	∞	±10	±4	-10 to 70
QB 694	3	20 to 60	∞	±10	±25	-40 to 85
QB 695	3	20 to 60	∞	±10	±30	-55 to 100
QB 696	3	20 to 60	∞	±10	±5	5 to 55
QB 697	3	20 to 60	∞	±10	±10	-10 to 70
QB 698	3	20 to 60	∞	±10	±30	-40 to 85
QB 699	3	20 to 60	∞	±10	±40	-55 to 100